

ASM170 Auto Start Module



Features

- Ideal For All Basic Auto-Start/Stop
- Programmable Multifunction Output
- Extended Operating Temperature Range
- Excellent Low Voltage Performance
- Compact Size Retrofits Existing ASM150 Installations
- Built-In Manual-Off-Auto Toggle Switch
- Smart FET Outputs Description

The **ASM170** is a compact yet powerful engine auto-start module. It offers flexibility and features normally found in much larger and more expensive units. Its high density MOLEX plug makes it ideal for panel builders. It can also be easily replaced in the field if problems should arise.

With the on-board Manual-Off-Automatic switch, Panel wiring is greatly simplified.

Its unique design also allows it to draw virtually no current in standby mode, yet be able to auto-start based on a sustained or momentary contact closure.

Features

The ASM170 is typically used in generator applications but can be applied anywhere a basic auto-start operation is required. Basic functions include engine crank/rest, crank disconnect, overspeed, low oil pressure, high engine temperature, low levels and spare shutdowns. The start signal to the controller can be momentary or sustained.

It also has a multifunction output that can be selected to perform one of the following functions:

- Glowplug
- Warmup/Cooldown
- Warmup
- Cooldown
- Choke
- Air Damper Shutoff

Specifications

Power Input: 6 to 28 VDC.

Power Consumption Standby: <1 mA.

Operating Temperature: -40 to 185°F (-40 to +85°C).

Inputs: Ground or positive inputs for high temperature, low oil pressure, High/Low Level, Auxiliary/Remote Stop sensors.

Lamp Test: When unit is powered up in Manual or Auto, the LED's light for 1 second as a test.

Outputs: 5A smart FET for cranking and multifunction output. 10A smart FET for Fuel Valve (Energized to Run) output. All 3 supply battery "+" 125 mA transistor for common failure, engine run, and auxiliary output. (Sink to battery "-")

Crank Attempts: Selectable for 3, 5, 10, or 255.

Crank/Rest Cycle Timing: Field adjustable 1 to 30 seconds.

Multifunction Output: Field programmable to one of the following options: Glowplug, Cooldown, Warmup/Cooldown, Warmup, Air gate – Overspeed Only, Air gate – Always, Choke, or Auxiliary Run output.

Shutdown Lockout Time Delay: Field adjustable 1 to 300 seconds. Locks out low oil pressure, high temperature, and loss of speed shutdowns on start-up.

Crank Disconnect Speed Setting: From 13 to 2500 Hz.

Overspeed Trip Point Setting: From 13 to 8500 Hz.

Speed Sensing Input: 1.5VAC RMS to 140 VAC RMS.

Shipping Weight: 1 lb. (.45 kg.)

Shipping Dimensions: 6.25 x 6.25 x 4.5 in. (159 x 159 x 114 mm).



CAUTION: Certain danger to human and to equipment such as applied in a mobile or marine application may occur if some equipment is stopped without pre-warning. It is therefore, recommended that monitored functions be limited to alarm only or to alarm before shutdown in such applications.



ASM170
w/o Toggle Switch

How to Order:

40700271	00009126 ASM170 Standard with Toggle Switch
40700272	00009347 ASM170 without Toggle Switch

NOTE: P/N 40000138 connector and 4 ft. wire harness must be ordered separately if required.

ENOVATION CONTROLS CORPORATE HEADQUARTERS
5311 S 122ND EAST AVENUE
TULSA, OK 74146

ENOVATION CONTROLS – SAN ANTONIO OFFICE
5757 FARINON DRIVE
SAN ANTONIO, TX 78249

ENOVATION CONTROLS – HOUSTON OFFICE
105 RANDON DYER RD
ROSENBERG, TX 77471

ENOVATION CONTROLS LTD. – UNITED KINGDOM
CHURCH ROAD LAVERSTOCK
SALISBURY SP1 1QZ UK

MURPHY ECONTROLS TECHNOLOGIES (HANGZHOU) CO, LTD.
77 23RD STREET
HANGZHOU ECONOMIC & TECHNOLOGICAL DEVELOPMENT AREA
HANGZHOU, ZHEJIANG 310018 CHINA

DOMESTIC SALES & SUPPORT

ECONTROLS PRODUCTS
PHONE: 210 495 9772
FAX: 210 495 9791
EMAIL: INFO@ECONTROLS.COM
WWW.ECONTROLS.COM

MURPHY PRODUCTS
PHONE: 918 317 4100
FAX: 918 317 4266
EMAIL: SALES@FWMURPHY.COM
WWW.FWMURPHY.COM

MURPHY CONTROL SYSTEMS & SERVICES
PHONE: 281 633 4500
FAX: 281 633 4588
EMAIL: CSS-SOLUTIONS@FWMURPHY.COM

MURPHY INDUSTRIAL PANEL DIVISION
PHONE: 918 317 4100
FAX: 918 317 4124
EMAIL: IPDSALES@FWMURPHY.COM

INTERNATIONAL SALES & SUPPORT

UNITED KINGDOM
PHONE: +44 1722 410055
FAX: +44 1722 410088
EMAIL: SALES@ENOVATIONCONTROLS.EU
WWW.FWMURPHY.EU

CHINA
PHONE: +86 21 6237 5885
FAX: +86 21 6237 5887
EMAIL: APSALES@FWMURPHY.COM

LATIN AMERICA & CARIBBEAN
PHONE: 918 317 2500
EMAIL: LASALES@FWMURPHY.COM

SOUTH KOREA
PHONE: +82 70 7951 4100
EMAIL: SKOREASALES@FWMURPHY.COM

INDIA
PHONE: +91 91581 37633
EMAIL: INDIASALES@FWMURPHY.COM

**ISO 9001
REGISTERED**



USA (TULSA) - ISO 9001:2008 FM 28221
USA (ROSENBERG) - ISO 9001:2008 FM 28221
UK-ISO 9001:2008 FM 29422
CHINA-ISO 9001:2008 FM 523851
Registered Facilities

Printed in the USA